

FEATURES & BENEFITS CHECKLIST



Features	Poolside	e Tech	Pentair			Hayward			Jandy		
- Catalos	Attendant	Mini	Intelli-	Easy Touch	Intelli-	Omni Hub	Omni PL	Omni Logic	A'Link TCX	A'Link PDA	A'Link RS
Water & Chemistry Management			Cilect	Touch	Center	1100		Logic	ICA	FDA	N3
Smart Filtration cycles for more effective filtration based on run-time and/or turnover rate	\oslash	\odot	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
Chemistry monitoring (pH & ORP) for water that's always safe and healthy	\oslash	\bigcirc		\otimes					\otimes	\otimes	
Customized chemical dosing. Integrate your preferred dosing devices for perfect water balance	\oslash	\oslash	×	\otimes	×	\otimes	\times	\otimes	×	\otimes	\otimes
Auto smart-dosing automatically increases pump speed when dosing and mixing to prevent staining	\oslash	\bigcirc	\times	\otimes	\otimes	\times	\otimes	\otimes	×	\otimes	\otimes
Chemistry Management for 2 bodies of water. NSF approved for commercial applications	\odot	\oslash	\otimes	\times	\bigcirc^1	\otimes	\times	\otimes	\otimes	\otimes	\bigcirc^1
Supports All Makes of Salt Chlorination	\bigcirc	\bigcirc	\otimes	\otimes	\times	\otimes	\otimes	\otimes	\times	\otimes	\otimes
Smart Freeze Protection enables individual control over specific features or separate 'bodies of water'	\oslash	\bigcirc	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
Accurate Flow Monitoring	⊘ ²	⊘ ²	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
Energy Management & Heating											
Smart heating management calculates the most efficient schedule to heat/cool your pool based on weather conditions & energy costs	\oslash	\bigcirc	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
Support for virtually any model heater/chiller	\bigcirc	\bigcirc	\otimes	×	×	×	\otimes	\otimes	\otimes	\otimes	\otimes
Energy costs and consumption are tracked by device, to better understand your power consumption	\oslash	\bigcirc	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
System can estimate the cost to heat or chill prior to an event for more conscious energy management	\oslash	\oslash	\times	\otimes	×	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
'Ready by' heater/chiller scheduling will have your pool or spa ready to use when you want it, at the lowest cost possible	\oslash	\oslash	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
Lighting											
The Attendant works with virtually ALL legacy (non-DMX) lighting systems using high voltage relays	\bigcirc	\bigcirc	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
DMX Compatible for the most advanced lighting control and features, no matter how big or small the project may be	\oslash	\oslash	\times	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\times	\otimes
Smart sync to Spotify® - Sync your DMX lights to Spotify® so they dance to the beat of your favorite tunes	\oslash	\bigcirc	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
Advanced color palette selection & dimming for instant control over 16M color palette & 20 dimming levels	\oslash	\bigcirc	\times	×	\otimes	\otimes	\otimes	\otimes	\times	\otimes	
Up to 128 independent zones to manage sophisticated lighting projects effortlessly through one simple user interface	\oslash	\bigcirc	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
Programmable - Create your own light shows for the ideal atmosphere	· Ø	\bigcirc	\otimes	\otimes	\otimes	×	\otimes	\otimes	\otimes	\otimes	

Needs an additional add on that communicates with the automation
 Requires a FlowVis with Digital Sensor & Pro Chem board
 Only with Jandy Infinite Water Color Lights & Transformer

^{4.} Cannot set a start time and end time with this automation in simple mode 5. Can only do Over The Air updates once software is updated by USB Device 6. Manufacturer specific limits may apply

Features		Poolside Tech		Pentair			Hayward			Jandy		
		Attendan	t Mini	Intelli- C'nect	Easy Touch	Intelli- Center	Omni Hub	Omni PL	Omni Logic	A'Link TCX	A'Link PDA	A'Link RS
Additional	Features											
	ows you to grant permissions to Guests v or prevent access to devices or functions	\bigcirc	\bigcirc	\times	\otimes					\times	\otimes	\otimes
	trol over Valve Actuators. Get full atrol over actuators from the App	\bigcirc	\oslash	\otimes	\times	\otimes	×	\otimes	\times	\otimes	×	\otimes
	Monitoring will alert the user of a down the pump to prevent damage	\bigcirc	\bigcirc	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes	\times
	r Leveling means The Attendant only and solenoid kit and will alert users ted	\oslash	\oslash	\otimes	×	\otimes	×	×	×	\otimes	×	×
	stics provide access for the Servicer es without having to be at the site	\bigcirc	\bigcirc	\otimes	\otimes	×	\otimes	\otimes	\otimes	\otimes	\otimes	\otimes
	etion automatically disables features over is closed, without the need ogramming	\oslash	\oslash	\otimes	×	\otimes	\otimes	\otimes	×	\otimes	×	×
Over the Air Up	dates automatically enure ays up to date	\bigcirc	\oslash	\otimes	\otimes	5	S 5	5	5	\otimes	\otimes	\otimes
Devices/Connectivity Can control virtually ALL device makes & models		\oslash	\otimes	8	\otimes	⊗	\otimes	\otimes	\otimes	\otimes	\otimes	⊗
Equipment Control Specs												
Variable Speed Pump Controls	*Control VS Pumps without using up *Ability to control Commercial VFD Devices	No ⁶ Limit	No ⁶ Limit		8	16	3	8	16		4	16
Bodies of water	*Control of individual bodies of water (Pool, spa, pond, fountain, etc)	No Limit	No Limit	1	2	1-2	2	4	4	1	1-2	1-2
High Voltage Relays	*High Voltage relays to control devices such as blowers, legacy lighting, or chemical pumps	2-8	2	2	3	4-10	3	4-6	4-10		3-7	3-7
Actuators	*Automatically move valves with 24V valve actuators	5	3	0	4	4-10	2	4	4	1	4	4
Flow Switch Ports	*Flow switch ports for flow switches, auto cover switches, or certain autofill sensors	5	2	0	0	0	1	1	2	0	0	0
Heaters	*Dry contact legacy heater connections for heaters without RS485	5	2			2		2	4			
Smart Heaters	*Gas heaters or Heat Pumps with RS485 Controls	No ⁶ Limit	No ⁶ Limit			16		4	4		2	2
Temperature Sensors	*Temperature sensor ports for 10K sensors or autofill sensors	5	2		3	3	3	3	4	3	4	4

- Needs an additional add on that communicates with the automation
 Requires a FlowVis with Digital Sensor & Pro Chem board
 Only with Jandy Infinite Water Color Lights & Transformer

- 4. Cannot set a start time and end time with this automation in simple mode 5. Can only do Over The Air updates once software is updated by USB Device 6. Manufacturer specific limits may apply



PHONE CONTACT 267-810-0600

○ LOCATION

560 Union Square Dr New Hope, PA 18938 info@poolside.tech
support@poolside.tech
marketing@poolside.tech

SOCIAL MEDIA

f Facebook @poolside.tech

O Instagram Opoolside.tech

n LinkedIn @poolside-tech

You Tuba (Opposidated